

**CSS Polymers, Inc.**  
**2659 Freedom Parkway, Ste 294**  
**Cumming, GA 30041**  
**Telephone: 770/645-0101 FAX: 866/694-3504**

**MATERIAL SAFETY DATA SHEET**

**I. CHEMICAL PRODUCT IDENTIFICATION**

Company: CSS Polymers, Inc. 2659 Freedom Parkway, Ste. 294, Cumming, GA 30041  
Product Name: **Quick-Repair 15**-Component A: Isocyanate  
Product Code: HTPP205, HTPP160  
Chemical Family: Aromatic Isocyanate Pre-polymer  
Chemical Name: Isocyanic Acid, Polymethylene Polyphenylene Ester  
Synonyms: Polymeric Diphenylmethane Diisocyanate (MDI)  
CAS No: 9016-87-9  
Formula: Not Applicable

**II. COMPOSITION/INFORMATION ON INGREDIENTS**

**Hazardous Ingredients**

| Ingredient Name/CAS No.                                 | Exposure Limits   | Concentration   |
|---|---|-----------------|
| 4,4 -Diphenylmethane Diisocyanate<br>101-68-8           | OSHA: 0.02 ppm Ceiling<br>0.20 mg/m <sup>3</sup> Ceiling<br><br>ACGIH: 0.005 ppm TWA<br>0.051 mg/m <sup>3</sup> TWA | Upper Bound 20% |
| .....   |   |                 |
| Higher Oligomers of MDI<br>9016-87-9                    | OSHA: Not Established<br>ACGIH: Not Established   | 30-35%          |
| .....   |   |                 |
| Diphenylmethane Diisocyanate (2,2'; 2,4')<br>26447-40-5 | OSHA: Not Established<br>ACGIH: Not Established   | 0-5%            |
| Aromatic Petroleum<br>64742-94-5                        | OSHA: Not Established<br>ACGIH: Not Established   | 15-40%          |

### III. HAZARDS IDENTIFICATION

#### Emergency Overview

WARNING: Color: Dark Brown; Form: Liquid; Odor: Slightly Musty Odor; May cause eye, skin and respiratory tract irritation; Harmful if inhaled; May cause allergic skin reaction; May cause lung damage; Use cold water spray to cool fire-exposed containers to minimize the risk of rupture; Toxic gases/fumes are given off during burning or thermaldecomposition; Closed container may explode under extreme heat.

#### POTENTIAL HEALTH EFFECTS:

Route(s) Of Entry.....Skin: Contact from liquid and aerosols (spray application).  
Inhalation: Although MDI is low in volatility, an inhalation hazard can exist from MDI aerosols or vapors formed during heating, foaming or spraying.

#### Human Effects and Symptoms of Overexposure:

Acute Inhalation:.....MDI vapors or mist at concentrations above the TLV can irritate (burning sensation) the mucous membranes in the respiratory tract (nose throat, lungs) causing runny nose, sore throat, coughing, chest discomfort, shortness of breath and reduced lung function (breathing obstruction). Persons with a pre-existing, nonspecific bronchial hyperactivity can respond to concentrations below the TLV with similar symptoms as well as asthma attack. Exposure well above the TLV may lead to bronchitis, bronchial spasm and pulmonary edema (fluid in lungs). These effects are usually reversible. Chemical or hypersensitive pneumonitis, with flu-like symptoms ( e.g., fever, chills) has also been reported. These symptoms can be delayed up to several hours after exposure.

Chronic Inhalation:.....: As a result of previous repeated overexposures or a single large dose, certain individuals develop isocyanate sensitization (chemical asthma) which will cause them to react to a later exposure to isocyanate at levels well below the TLV. These symptoms, which can include chest tightness, wheezing, cough, shortness of breath or asthma attack, could be immediate or delayed (up to several hours after exposure). Similar to many non-specific asthmatic responses, there are reports that once sensitized an individual can experience these symptoms upon exposure to dust, cold air or other irritants. This increased lung sensitivity can persist for weeks and in severe cases for several years. Overexposure to isocyanates has also been reported to cause lung damage (including decrease in lung function) which may be permanent. Sensitization can either be temporary or permanent.

Acute Skin Contact.....: Isocyanates react with skin protein and moisture and can cause irritation which may include the following symptoms: reddening, swelling, rash, scaling or blistering. Cured material is difficult to remove.

Chronic Skin Contact.....: Prolonged contact can cause skin reddening, swelling, rash scaling, blistering and in some cases, skin sensitization. Individuals who have skin

sensitization can develop these symptoms from contact with liquid or vapors. Animal tests have indicated that respiratory sensitizations can result from skin contact with MDI. This data reinforces the need to prevent direct skin contact with MDI. (See Toxicological Information, Sensitization).

Acute Eye Contact .....: Liquid, aerosols or vapors are irritating and can cause tearing, reddening and swelling. If left untreated, corneal damage can occur and the injury is slow to heal. However, damage is usually reversible. See First Aid measures for treatment.

Chronic Eye Contact.....: None Found.

Acute Ingestion.....: Can result in irritation and corrosive action in the mouth, stomach tissue and digestive tract. Symptoms can include sore throat, abdominal pain, nausea, vomiting and diarrhea.

Chronic Ingestion.....: None Found.

Carcinogenicity.....: Neither MDI nor polymeric MDI are listed by the NTP, IARC or regulated by OSHA as carcinogens. See two year inhalation study in Toxicological Information, Carcinogenicity.

Medical Conditions Aggravated By Exposure: Asthma, other respiratory disorders (bronchitis, emphysema, bronchial hyperreactivity), skin allergies, eczema.

#### **For Petroleum Distillate:**

Eye: ...Direct eye contact may cause minor irritation but no corneal injury. Symptoms include stinging, tearing, redness and swelling of the eye.

Skin:...Can cause skin irritation. Prolonged or repeated contact causes dry skin. Symptoms may include redness, burning, drying and cracking of skin. May cause allergic skin reaction (delayed skin rash which may be followed by blistering or scaling). Passage of this material into the body through the skin is possible but unlikely to result in any harmful effects during safe handling of this product.

Inhalation: Breathing of vapor of this material may be harmful.

Symptoms of Exposure: Exposure to the petroleum distillate through breathing, Swallowing and/or passage through the skin may cause sweating, fever, upset stomach or intestinal tract (nausea, vomiting, diarrhea) irritation (nose, throat, airways), lung irritation, central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness), abdominal pain, frequent or painful urination, confusion, blood abnormalities (breakage of red blood cells), kidney damage, lung damage, respiratory failure.

Target Organ Effects: The petroleum distillate has been shown to lower activity of certain immune system cells in experimental animals. The significance of this effect with respect to human health is uncertain. Overexposure to this material has been suggested as a cause of the following effects in laboratory animals: mild, reversible liver and kidney effects, cataracts, anemia, nasal damage, central nervous system damage. Overexposure has been suggested as a cause of the following in humans: cataracts, eye damage.

Primary Route(s) of Entry: Eyes, skin, Inhalation, Ingestion.

#### **IV. FIRST AID MEASURES**

First Aid For Eyes.....: Flush with copious amounts of water, preferably luke warm water for at least 15 minutes, holding eyelids open all the time. Refer individuals to physician or ophthalmologist for immediate follow-up.

First Aid For Skin.....: Remove contaminated clothing. Wash affected skin thoroughly with soap and water. Wash contaminated clothing thoroughly before re-use. For severe exposures, get under safety shower after removing clothing, then get medical attention. For lesser exposures, seek medical attention if irritation develops or persists after the area is washed.

First Aid For Inhalation.....: Move to an area free from risk of further exposure. Administer oxygen or artificial respiration as needed. Obtain medical attention. Asthmatic-type symptoms may develop and maybe immediate or delayed upto several hours. Consult physician should this occur.

First Aid For Ingestion.....: ***Do not induce vomiting***. Give 1 to 2 cups of milk or water to drink. ***Do not give anything by mouth to an unconscious person***. Consult physician.

Note To Physician.....: Eyes. Stain for evidence of corneal injury. If cornea is burned, instill antibiotic steroid preparation frequently. Workplace vapors have produced reversible corneal epithelial edema impairing vision. Skin. This compound is a known skin sensitizer. Treat symptomatically as for contact dermatitis or thermal burn. Ingestion. Treat symptomatically. There is no specific antidote. Inducing vomiting is contraindicated because of the irritating nature of this compound. Respiratory. This compound is a known pulmonary sensitizer. Treatment is essentially symptomatic. An individual having a skin or pulmonary sensitization reaction to this material should be removed from exposure to any isocyanate.

#### **For Petroleum Distillate**

Eyes:...Flush with copious amounts of water for at least 15 minutes. Consult Physician.

Skin:...Wash material off with plenty of soap and water. Consult physician if irritation persists. Do not apply grease or ointments. Launder clothing before re-use.

Inhalation: Move to an area free from risk of further exposure. Seek medical attention.

Ingestion: **DO NOT INDUCE VOMITING**. If person is conscious and can swallow, immediately give two glasses of water. Never give anything by mouth to an unconscious person. Consult physician.

Note to Physician: The petroleum distillate is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity when deciding whether to induce vomiting. Inhalation or ingestion of high levels of this material may cause a hemolytic reaction. Complications of acute intravascular hemolysis

include anemia, leukocytosis, fever, hemoglobinuria, jaundice, renal insufficiency and sometimes disturbances in liver function. Pre-existing disorders of the following organs may be aggravated by exposure to this material: respiratory tract, skin, lung(e.g. asthma like conditions), kidney, immune system, eye. Exposure to this material may aggravate any pre-existing condition sensitive to a decrease in available oxygen, such as chronic lung disease, coronary artery or anemia. Individuals with erythrocyte glucose-6-phosphate dehydrogenase deficiency are particularly susceptible to hemolytic agents and rapidly develop hemolytic anemia from ingestion or inhalation of this material.

## **V. FIRE FIGHTING MEASURES**

- Flash Point.....: 415<sup>0</sup> F (213<sup>0</sup> C) Pensky-Martens Closed Cup (ASTM D-93)
- Extinguishing Media.....: Dry Chemical; Carbon Dioxide, Foam, Water Spray for large fires.
- Special Fire Fighting Procedures:.....: Full emergency equipment with self-contained breathing apparatus and full protective clothing should be worn by fire fighters. During a fire, MDI vapors and other irritating and highly toxic gases may be generated by thermal decomposition and combustion. (See Stability and Reactivity). At temperatures above 400<sup>0</sup> F (204<sup>0</sup> C), polymeric MDI can polymerize and decompose which can cause pressure build-up in closed containers. Explosive rupture is possible. Therefore, use cold water to cool fire-exposed containers.

**Emergency Numbers: INFOTRAC 800.535.5035**

## **VI. ACCIDENTAL RELEASE MEASURES**

Spill or Leak Procedures.: Evacuate and ventilate spill area; dike spill to prevent entry into water system; wear full protective equipment, including respiratory equipment during clean-up. (See Employee Protection Recommendations). Major Spill: If transportation spill, call INFOTRAC at 800/535-5053. If temporary control of isocyanate vapor is required, a blanket of protein foam (available at most fire departments) may be placed over the spill. Large quantities may be pumped into closed but not sealed, container for disposal. Minor Spill: Absorb isocyanates with sawdust or other absorbent, shovel into suitable unsealed containers, transport to well-ventilated area (outside) and treat with neutralizing solution: mixture of water (80%) with non-ionic surfactant Surfonic N-95 (20%), or ; water (90%), concentrated ammonia (3-8%), and detergent (2%). Add about 10 parts of neutralizer per part of isocyanate, with mixing. Allow to stand uncovered for 48 hours to let carbon dioxide escape. Clean-up: Decontaminate floor with decontamination solution letting stand for at least 15 minutes

## **VII. HANDLING AND STORAGE**

Storage Temperature (Min/Max): 64<sup>0</sup> F (18<sup>0</sup> C)/ 86<sup>0</sup> F (30<sup>0</sup> C)

Shelf Life.....: 6 months

Special Sensitivity.....: If container is exposed to high heat, 400<sup>0</sup> F (204<sup>0</sup> C) it can be pressurized and possibly rupture. MDI reacts slowly with water to form carbon dioxide gas. This gas can cause sealed containers to expand and possibly rupture.

Handling/Storage Precautions.....: Store in tightly closed containers to prevent moisture contamination. Do not reseal if contamination is suspected. Avoid contact with skin and eyes. Do not breathe aerosols or vapors. Warning properties (irritation of the eyes, nose and throat or odor) are not adequate to prevent chronic overexposure from inhalation. This material can produce asthmatic sensitization upon either single inhalation exposure to a relatively high concentration or upon repeated inhalation exposures to lower concentrations. Exposure to vapors of heated MDI can be extremely dangerous. Employee education and training in the safe use and handling of this compound are required under the OSHA Hazard Communication Standard.

## **VIII. PERSONAL PROTECTION**

Eye Protection Requirements.....: Liquid chemical goggles. Vapor resistant goggles should be worn when contact lenses are in use. In a splash hazard environment chemical goggles should be used in combination with a full face-shield.

Skin Protection Requirements....: Permeation resistant gloves (butyl rubber, nitrile Rubber, polyvinyl alcohol). However, please note that PVA degrades in water. Cover as much of the exposed skin area as possible with appropriate clothing. If skin creams are used, keep the area covered by the cream to a minimum.

Ventilation Requirements.....: Local exhaust should be used to maintain levels below the TLV whenever MDI is processed, heated or spray applied. Standard reference sources regarding industrial ventilation (i.e., ACGIH Industrial Ventilation) should be consulted for guidance about adequate ventilation.

Respirator Requirements.....: Concentrations greater than the TLV can occur when MDI is sprayed, heated or used in a poorly ventilated area. In such cases, or whenever concentrations of MDI exceed the TLV or are not known, respiratory protection must be worn. A supplied air respirator (either positive pressure or continuous flow type) is required. In an emergency situation, a self-contained breathing apparatus may be used. MDI has poor warning properties, since the concentration at which MDI can be smelled is substantially higher than the maximum exposure limit. Observe OSHA regulations for respirator use (29 CFR 1910.134).

Monitoring.....: Isocyanate exposure levels must be monitored. Monitoring of airborne isocyanates in the breathing zone of individuals should

become part of the overall employee exposure characterization program. Monitoring techniques have been developed by NIOSH, and OSHA. Upon request, HiTherm can make available methods which are modifications of these NIOSH and OSHA methods.

Medical Surveillance.....: Medical supervision of all employees who handle or come in contact with isocyanate is recommended. These should include pre-employment and periodic medical examinations with pulmonary function tests (FEV, FVC as a minimum). Persons with asthmatic-type conditions, chronic bronchitis, other chronic respiratory diseases or recurrent skin eczema or sensitization should be excluded from working with isocyanates. Once a person is diagnosed as sensitized to an isocyanate, no further exposure can be permitted.

Additional Protective Measures...: Safety showers and eyewash stations should be available. Educate and train employees in safe use of this product. Follow all label instructions. For additional information, contact HiTherm, LLC.

## **IX. PHYSICAL AND CHEMICAL PROPERTIES**

Physical Form.....: Liquid  
Color.....: Dark Brown  
Odor.....: Slightly musty odor  
Molecular weight.....: Trade Secret  
pH.....: Not Established  
Boiling Point.....: 406<sup>0</sup> F (208<sup>0</sup> C) at 5 mmHg for MDI  
Melting/Freezing Point.....: Below 32<sup>0</sup> F (0<sup>0</sup> C) for MDI  
Solubility in Water.....: Not Soluble. Reacts slowly with water to liberate carbon dioxide gas.  
Specific Gravity.....: 1.20 @ 77<sup>0</sup> F (25<sup>0</sup> C)  
Bulk Density.....: 10.0 lbs/gal  
% Volatile by Volume.....: Negligible  
Vapor Pressure.....: Less than 10<sup>-5</sup> mmHg at 77<sup>0</sup> F (25<sup>0</sup> C) for MDI  
Vapor Density.....: 8.2 (MDI) (Air = 1)

## **X. STABILITY AND REACTIVITY**

Stability.....: This is a stable material  
Hazardous Polymerization.....: May occur; Contact with moisture, other materials which react with isocyanates, or temperatures above 400<sup>0</sup> F (204<sup>0</sup> C), may cause polymerization.  
Incompatibilities.....: Water, amines, strong bases, alcohols. Will cause some corrosion to copper alloys and aluminum.  
Instability Conditions.....: Contamination with water.  
Decompositions Products.....: By high heat and fire: carbon monoxide, oxides of Nitrogen, traces of HCN, MDI vapors or aerosols.

## **XI. TOXICOLOGICAL INFORMATION**

Toxicity Data For: Diphenylmethane Diisocyanate (Monomeric and Polymeric)

### Acute Toxicity

Oral LD50.....: Greater than 10,000 mg/kg (Rat)

Dermal LD50.....: Greater than 6,200 mg/kg (Rabbit)

Inhalation LC50.....: The 4-hour LC50 for Polymeric MDI in rats ranges from 370 to 490 mg/m<sup>3</sup>. The 4-hour LC50 for monomeric MDI in rats was estimated to be between 172 and 187 mg/m<sup>3</sup>.

Eye Effects.....: Slight to moderate irritation.

Skin Effects.....: Slight to moderate irritation.

Sensitization.....: MDI has been shown to produce dermal sensitization in laboratory animals. Evidence of respiratory sensitization has also been observed in guinea pigs. In addition, there is some evidence suggestive of cross-sensitization between different types of diisocyanates.

Chronic Toxicity.....: In a combined chronic inhalation toxicity/oncogenicity study, rats were exposed to an aerosol of polymeric MDI for 6 hours per day, 5 days per week for one or two years. The exposure concentrations were 0, 0.2, 1.0 and 6 mg/m<sup>3</sup>. Microscopic examination of tissues revealed the effects of irritation to the nasal cavity and lungs in animals exposed to 1.0 and 6.0 mg/m<sup>3</sup>. The No Observable Effect Level (NOEL) was 0.2 mg/m<sup>3</sup>.

Carcinogenicity.....: In the study described above (See Chronic Toxicity), the occurrence of pulmonary adenomas and a single pulmonary adenocarcinoma was considered to be related to MDI. These tumors were observed only in rats exposed to the High concentration of 6.0 mg/m<sup>3</sup>.

Mutagenicity.....: Positive (Salmonella microsome test with metabolic activation; cell transformation assay) as well as negative (mouse lymphoma specific locus mutation test with or without metabolic activation) results have been observed "in-vitro". The use of certain solvents which rapidly hydrolyze MDI is suspected of producing mutagenicity in some of these studies. MDI was negative in an "in-vivo" (mouse micronucleus) assay.

Developmental Toxicity.....: Rats were exposed to polymeric MDI at air concentrations of 0, 1, 4 and 12 mg/m<sup>3</sup> during days 6-15 of gestation. Maternal Toxicity (including mortality) was observed at the highest concentration of 12 mg/m<sup>3</sup> accompanied by embryo and fetal toxicity. However, no teratogenic effects were observed even at this lethal concentration.

## **XII. ECOLOGICAL INFORMATION**

Ecology Data For: Diphenylmethane Diisocyanate (monomeric and Polymeric)

Aquatic Toxicity.....: LC50 – 24 hr. (static): Greater than 500 mg/liter for Daphne magna, Limnea Stagnalis and Zebra fish (Brachydanio rerio) for

both monomeric and polymeric MDI.

### **XIII. DISPOSAL CONSIDERATIONS**

Waste Disposal Method.....: Waste must be disposed of in accordance with federal, state and local environmental control regulations. Incineration is the preferred method.

Empty Container Precautions.: Empty containers must be handled with care due to product residue. Decontaminate containers prior to disposal. Empty decontaminated containers should be crushed to prevent reuse. ***Do not heat or cut empty container with electric or gas torch.*** (See Fire Fighting Measures and Stability and Reactivity). Gases may be highly toxic.

### **XIV. TRANSPORTATION INFORMATION**

Technical Shipping Name.....: Methylene diphenyl diisocyanate

Freight Class Bulk.....: Methylene diphenyl diisocyanate

Freight Class Package.....: Chemicals, NOI (Isocyanate), NMFC 60000

Product Label.....: Product Label Established

#### **DOT (Domestic Surface)**

Proper Shipping Name.....: Other Regulated Substances, Liquid, N.O.S.\*

Hazard Class or Division.....: 9

UN/NA Number.....: NA 3082

Packing Group.....: III

Hazardous Substance.....: MDI, (Methylene diphenyl diisocyanate)

DOT Product RQ lbs (kgs).....: 13888 lbs (6299.6 kgs)

Hazard Label (s).....: Class 9

Hazard Placard(s).....: Class 9

\* When in individual containers of less than the product RQ, this material ships as non-regulated.

IMO/IMDG CODE (Ocean

Hazard Class Division Number....: Non-Regulated

ICAO/IATA (Air)

Hazard Class Division Number....: Non-Regulated

### **XV. REGULATORY INFORMATION**

OSHA Status.....: This product is hazardous under the criteria of the Federal OSHA Hazard Communication Standard 29 CFR 1910.1200.

TSCA Status.....: On TSCA inventory.

CERCLA Reportable Quantity...: 5000 lbs for 4,4'- Diphenylmethane Diisocyanate, CAS # 101-68-8.

SARA Title III:

Section 302 Extremely Hazardous Substances...: NONE

Section 311/312

Hazard Categories.....: Immediate Health Hazard; Delayed Health Hazard.

Section 313

Toxic Chemicals.....: Polymeric Diphenylmethane Diisocyanate, CAS # 9016-87-9, 100%; Contained in this polymeric product is 4,4' – Diphenylmethane Diisocyanate, CAS # 101-68-8; Upper Bound 20%.

RCRA Status.....: MDI is not listed as a hazardous waste. To the best of Our Knowledge, MDI does not meet the criteria of a hazardous waste if discarded in its purchased form. However, under RCRA, it is the responsibility of the user of the products to determine, at the time of the disposal, whether a product meets any of the criteria for a hazardous waste. This is because product uses, transformations, mixtures, processes, etc., may render the resulting material hazardous, under the criteria of ignitability, corrosivity, reactivity and toxicity characteristics under the new Toxicity Characteristics Leaching Procedure (TCLP) 40 Code of Federal Regulations 261.20-24.

The following chemicals are specifically listed by individual states; other product specific health and safety data in other sections of the MSDS may also be applicable for state requirements. For details on your regulatory requirements you should contact the appropriate agency in your state.

| <u>Component Name/<br/>CAS Number</u>                   | <u>Concentration</u> | <u>State Code</u>             |
|---|----------------------|-------------------------------|
| 4,4' –Diphenylmethane Diisocyanate<br>101-68-8          | Upper Bound 20%      | PA1, FL, IL, MA, RI, NJ1, CN2 |
| Higher Oligomers of MDI<br>9016-87-9                    | 30-35%               | PA3, NJ4                      |
| Diphenylmethane Diisocyanate (2,2'; 2,4')<br>26447-40-5 | 0-5%                 | PA3, NJ4                      |

FL = Florida substance List  
 IL = Illinois Toxic Substances List  
 MA = Massachusetts Hazardous Substance List  
 NJ1 = New Jersey Hazardous Substance List  
 NJ4 = New Jersey Other- included in 5 predominant ingredients > 1%  
 PA1 = Pennsylvania Hazardous Substance List  
 PA3 = Pennsylvania Non-hazardous present at 3% or greater.  
 RI = Rhode Island List of Designated substances.  
 CN2 = Canada WHMIS Ingredient Disclosure List over 0.1%.

### **XVI. OTHER INFORMATION**

NFPA 704M Ratings:    Health            Flammability            Reactivity            Other  
    3                            1                            1                            0  
    0=Insignificant    1=Slight    2= Moderate    3= High    4=Extreme

HMIS Ratings:            Health            Flammability            Reactivity  
    3\*                            1                            1  
    0-Minimal    1=slight    2=Moderate    3= Serious    4= Severe  
    \* Chronic Health Hazard

California Proposition 65:

The following statement is made in order to comply with the California Safe Drinking Water and Toxic Enforcement Act of 1986: This product contains the following substance(s) known to the State of California to cause cancer:

BENZENE

This product contains the following substance(s) known to the State of California to cause reproductive harm:

BENZENE, TOLUENE

We believe that the information contained in this MSDS is current. Since the use of this information and the conditions of use of the product are not within our control, it is the obligation of the user to determine the conditions of safe use of this product. The information herein is given in good faith, but no warranty, expressed or implied, is made.

**CSS Polymers, Inc.**  
**2659 Freedom Parkway, Ste 294**  
**Cumming, GA 30041**  
**Telephone: 770/645-0101 FAX: 866/694-3504**

**MATERIAL SAFETY DATA SHEET**

**I. PRODUCT INFORMATION**

**PRODUCT:** Quick-Repair 15 Component B  
**DISTRIBUTOR:** CSS Polymers, Inc.  
2659 Freedom Parkway, Ste 294  
Cumming, GA 30041  
**TEL./FAX:** 770/645-0101 866/694-3504  
**CHEMICAL NAME:** Polyether Polyol Blend  
**CHEMICAL FAMILY:** Urethane System Resin Component

**MOL. WT.:** N/A  
**FORMULA:** Mixture  
**DATE:** May 2007

**II. HAZARDOUS COMPONENTS**

| <b>Component</b>                                      | <b>CAS NO.</b> | <b>PEL-Source</b> | <b>Concentration</b> |
|---|----------------|-------------------|----------------------|
| <b>Composition of this Formula is a Trade secret.</b> |                |                   |                      |
| Polyether Polyol                                      | 25791-96-2     | Not Established   | Trade Secret         |
| Polyether Polyol                                      | 102-60-3       | Not Established   | Trade Secret         |
| Organo Metal Catalyst                                 | 34364-26-6     | Not Established   | 0-1.5%               |
| Aromatic Petroleum                                    | 64742-94-5     | Not Established   | 15-35%               |

**III. PHYSICAL DATA**

Boiling Point.....: Not Established  
Specific Gravity/ Bulk Density.....: 1.05 (H<sub>2</sub>O=1)  
Vapor Pressure, mm Hg @ 20<sup>0</sup>C.....: Less than 1.0  
Solubility in H<sub>2</sub>O.....: Soluble  
Appearance.....: Colorless liquid

#### **IV. FIRE AND EXPLOSION HAZARD DATA**

Flash Point/Method.....: 350<sup>0</sup> F, PMCC  
Flammable Limits(STP).....: Not Determined  
Extinguishing Media.....: CO<sub>2</sub>, Dry Chemical, Foam Water Fog  
Fire & Explosion Hazard.....: Low Hazard  
Special Fire Fighting Procedures.....: Turnout gear, self-contained breathing apparatus for protection against suffocation and toxic decomposition products.

**Emergency Numbers: INFOTRAC 800.535.5035**

#### **V. HEALTH HAZARD DATA**

##### **For Petroleum Distillate:**

**Eye:** Direct eye contact may cause minor irritation but no corneal injury. Symptoms include stinging, tearing, redness and swelling of the eye.

**Skin:** Can cause skin irritation. Prolonged or repeated contact causes dry skin. Symptoms may include redness, burning, drying and cracking of skin. May cause allergic skin reaction (delayed skin rash which may be followed by blistering or scaling). Passage of this material into the body through the skin is possible but it is unlikely to result in any harmful effects during safe handling of this product.

**Inhalation:** Breathing of vapor of this material may be harmful.

**Symptoms of Exposure:** Exposure to the petroleum distillate through breathing, swallowing and/or passage through the skin may cause sweating, fever, upset stomach or intestinal tract (nausea, vomiting, diarrhea), irritation (nose, throat, airways), lung irritation, central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness), abdominal pain, frequent or painful urination, confusion, blood abnormalities (breakage of red blood cells), kidney damage, lung damage, respiratory failure.

**Target Organ Effects:** The petroleum distillate has been shown to lower activity of certain immune system cells in experimental animals. The significance of this effect with respect to human health is uncertain. Overexposure to this material has been suggested as a cause of the following effects in laboratory animals: mild, reversible liver and kidney effects, cataracts, anemia, nasal damage, central nervous system damage. Overexposure has been suggested as a cause of the following in humans: cataracts, eye damage.

**Primary Route(s) Of Entry:** Eyes, Skin, Inhalation, Ingestion

##### **Emergency and First Aid Procedures:**

**Eyes:** Flush with copious amounts of water for at least 15 minutes. Consult physician.

**Skin:** Wash material off of the skin with plenty of soap and water. Consult physician if irritation persists. Do not apply grease or ointments. Launder clothing before re-use.

**Inhalation:** Move to an area free from risk of further exposure. Seek medical attention.

**Ingestion: DO NOT INDUCE VOMITING.** If person is conscious and can swallow, immediately give two glasses of water. If vomiting occurs, keep patients head lower than hip level to prevent aspiration of fluids into the lungs. Never give anything by mouth to an unconscious person. Consult physician.

**Note to Physician:** The petroleum distillate is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity when deciding whether to induce vomiting. Inhalation or ingestion of high levels of this material may cause a hemolytic reaction. Complications of acute intravascular hemolysis include anemia, leukocytosis, fever, hemoglobinuria, jaundice, renal insufficiency and sometimes disturbances in liver function. Pre-existing disorders of the following organs may be aggravated by exposure to this material: respiratory tract, skin, lung (for example, asthma-like conditions), kidney, immune system, eye. Exposure to this material may aggravate any pre-existing condition sensitive to a decrease in available oxygen, such as chronic lung disease, coronary artery disease or anemia. Individuals with erythrocyte glucose-6-phosphate dehydrogenase deficiency are particularly susceptible to hemolytic agents and rapidly develop hemolytic anemia from ingestion or inhalation of this material.

## **VI. REACTIVITY DATA**

**Stability**.....: Stable under normal conditions.

**Hazardous Decomposition Products**.....: CO, CO<sub>2</sub>, NO<sub>x</sub>, SO<sub>2</sub>, SO<sub>3</sub>, H<sub>2</sub>S

**Incompatibility**(chemicals to avoid).....: Strong acids and oxidizing agents.

**Hazardous Polymerization**.....: Will not occur.

## **VII. SAFE HANDLING AND USE INFORMATION**

Eye Protection.....: Safety glasses or goggles required; do not wear contact lenses.

Skin Protection.....: Impervious clothing and gloves to prevent skin contact.

Ventilation.....:Required to maintain vapors below irritating levels.

Respiratory Protection: A NIOSH/MSHA approved respirator (negative pressure type).

Containers of this blend may be hazardous when emptied. Since empty containers retain product residues, all hazard precautions given in the data sheet must be observed.

## **VIII. SPILL OR LEAK PROCEDURES**

**Spill and Leak Procedures:** Dike with absorbent material and place in overpack for disposal.

**Waste Disposal:** Dispose of according to local state and federal regulations. Under the CERCLA/RCRA regulations currently in effect, this product is not regulated as a hazardous material.

## **IX. FEDERAL REGULATORY INFORMATION**

**TSCA:** All components in this mixture are listed on the inventory.

**SARA HAZARD CATEGORY:** Immediate health, Delayed health, Fire.

**NFPA Hazard Rating:**

| <b>Health</b>    | <b>Fire</b> | <b>Reactivity</b> | <b>Other</b> |           |
|------------------|-------------|-------------------|--------------|-----------|
| <b>3</b>         | <b>1</b>    | <b>0</b>          | <b>0</b>     |           |
| 0= Insignificant | 1=Slight    | 2=Moderate        | 3=High       | 4=Extreme |

**California proposition 65:**

The following statement is made in order to comply with the California Safe Drinking Water and Toxic Enforcement Act of 1986: This product contains the following substance(s) known to the State of California to cause cancer:

BENZENE

This product contains the following substance(s) known to the State of California to cause reproductive harm:

BENZYNE, TOLUENE

We believe that the information contained in this MSDS is current. Since the use of this information and the conditions of use of the product are not within our control, it is the obligation of the user to determine the conditions of safe use of this product. The information herein is given in good faith, but no warranty, expressed or implied, is made.